



## AIR-DRYING SUPER GLOSS ENAMEL

### Features

- Made with high quality lightfast pigments
- Low VOC
- High Quality Gloss Finish
- Can be scrubbed using soap and warm water
- Excellent gloss retention under most severe conditions

### Recommended for

For interior use on primed or previously painted wood, metal surfaces

### General Description

Al Khaleej Super Gloss Enamel produces a hard, durable finish with maximum gloss retention. It has excellent brushability and opacity. Al Khaleej Super Gloss Enamel can be applied on prepared and primed surfaces such as wood, metal, cement plaster, asbestos, cement sheets, hard board etc. Before applying the paint, it should be ensured that the surface is clean, dry and free from dust, grease and rust. Will not chip off or peel away. Will not discolor or chalk. Offers excellent resistance to polluted environments, and direct flames. **This is a single component product. Do not mix with any other product. Thin only with the recommended thinner.**

### Limitations

Do not paint if temperature is within 3°C of dew point, or if rain is expected within 5 hours of application.

### TECHNICAL DATA

<b>Generic Type</b>	Gloss Enamel paint	<b>Dries by</b>	Air Dried
<b>Specific Gravity</b>	1.12 ± 0.2 kg/ltr	<b>Finish</b>	High Gloss
<b>Coverage per ltr</b>	95 – 105 Sq. Ft.at Recommended DFT	<b>Surface Temperature at Application</b>	Min. 10°C
<b>Recommended Film Thickness</b>	Wet: 65 ± 5 microns		Max. 35°C
	Dry: 45 ± 5 microns	<b>Thinner</b>	Spirit/Turpentine Oil/Al Khaleej Thinner for Enamels
<b>Drying Time @ 30°C</b>	To Touch: 2 hours	<b>Storage Temperature</b>	Min. 15°C
	Hard Dry: 12 to 14 Hours		Max. 32°C
	To Recoat: 16 to 18 hours	<b>Recommended Primers</b>	Al Khaleej Alkyd Red Oxide Primer

**KEEP OUT OF REACH OF CHILDREN  
FOR PROFESSIONAL USE ONLY**